


SOT-23 Plastic-Encapsulate Diodes

• Features

- Fast Switching Speed
- For General Purpose Switching Applications
- High Conductance



SOT - 23

• MAXIMUM RATINGS (T_C=25°C)

Parameter	Symbol	Limit	Unit
Reverse Voltage	V _R	70	V
Forward Current	I _F	200	mA
Non-Repetitive Peak Forward Surge Current @t=8.3ms	I _{FSM}	2.0	A
Power Dissipation	P _D	225	mW
Thermal Resistance Junction to Ambient	R _{θJA}	556	°C/W
Thermal Resistance Junction to Case	R _{θJC}	26	°C/W
Operation Junction and Storage Temperature Range	T _J , T _{STG}	-55~+150	°C





• ELECTRICAL CHARACTERISTICS (T_a=25°C)

Parameter	Symbol	Min	Typ	Max	Unit	Conditions
Reverse breakdown voltage	V _R	70			V	I _R =100μA
Forward voltage	V _{F1}			0.715	V	I _F =1mA
	V _{F2}			0.855	V	I _F =10mA
	V _{F3}			1	V	I _F =50mA
	V _{F4}			1.25	V	I _F =150mA
Reverse current	I _R			2.5	μA	V _R =70V
Capacitance between terminals	C _T			1.5	pF	V _R =0, f=1MHz
Reverse recovery time	t _{rr}			6	ns	I _F = I _R = 10mA, I _{rr} = 0.1 x I _R , R _L = 100Ω




• Ordering Information:

Part NO.	BAW56
Marking	A1
Packing Information	REEL TAPE
Basic ordering unit (pcs)	3000


• Typical Characteristics



SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°



Note:

1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.